

# MATERIAL SAFETY DATA SHEET

## Section I. Chemical Product and Company Identification

<b>Product Name</b>	Lanthanum Strontium Manganite / Cerium Gadolinium Oxide
<b>Product Code</b>	LSM/GDC
<b>CAS Number</b>	Mixture
<b>Manufacturer's Name</b>	NexTech Materials, Ltd.
<b>Address</b>	404 Enterprise Drive Lewis Center, OH 43035
<b>Emergency Telephone Number</b>	1-800-424-9300 (Chemtrec)
<b>Information Telephone Number</b>	614-842-6606
<b>Date Prepared</b>	August 13, 2004

## Section II. Composition / Information on Ingredients

Component	CAS #	% (Optional)
Lanthanum oxide	1312-81-8	
Manganese oxide	1317-35-7	
Strontium oxide	1314-11-0	
Cerium (IV) oxide	1306-38-3	
Gadolinium oxide	12064-62-9	

## Section III. Hazards Identification

- ◆ Hazard description: Irritant, Harmful
- ◆ Information pertaining to particular dangers for man and environment  
Irritating to eyes, respiratory system and skin.  
Harmful by inhalation, in contact with skin and if swallowed.

## Section IV. First Aid Measures

- ◆ **After inhalation**  
Supply fresh air. If required, provide artificial respiration. Keep patient warm.  
Seek immediate medical advice.
- ◆ **After skin contact**  
Immediately wash with water and soap and rinse thoroughly. Remove affected clothing.  
Seek immediate medical advice.
- ◆ **After eye contact**  
Rinse opened eye for several minutes under running water. Then consult a doctor.
- ◆ **After swallowing**  
Seek immediate medical advice.

## Section V. Fire Fighting Measures

- ◆ **Suitable extinguishing agents**  
Product is not flammable. Use fire-fighting measures that suit the surrounding fire.
- ◆ **Protective equipment:**  
Wear self-contained respirator.  
Wear fully protective impervious suit.

## Section VI. Accidental Release Measures

- ◆ **Suitable extinguishing agents** Extinguishing powder. Avoid use of water.
- ◆ **Special hazards caused by the material, its products of combustion or resulting gases:**  
Exothermic reaction with water *may* occur.
- ◆ **Protective equipment:**  
Wear self-contained respirator.  
Wear fully protective impervious suit.

## Section VII. Handling and Storage

- ◆ **Handling**

- ◆ **Information for safe handling:**  
Keep container tightly sealed.  
Store in cool, dry place in tightly closed containers.  
Ensure good ventilation at the workplace.
- ◆ **Information about protection against explosions and fires:**  
The product is not flammable
- ◆ **Storage**
- ◆ **Requirements to be met by storerooms and receptacles:**  
No special requirements.
- ◆ **Information about storage in one common storage facility:**  
Do not store together with oxidizing and acidic materials.  
Store away from water/moisture.
- ◆ **Further information about storage conditions:**  
This product is hygroscopic.  
Keep container tightly sealed.  
Store in cool, dry conditions in well sealed containers.

### Section VIII. Exposure Controls and Personal Protection

- ◆ **Additional information about design of technical systems:**  
Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute.
- ◆ **Components with limit values that require monitoring at the workplace:**

Component	Limit Values (mg/m <sup>3</sup> )	
	ACGIH TLV	OSHA PEL
Manganese, elemental & inorganic compounds (as Mn)	0.2	5-ceiling

- ◆ **Additional information:** No data
- ◆ **Personal protective equipment**
- ◆ **General protective and hygienic measures**  
The usual precautionary measures for handling chemicals should be followed.  
Keep away from foodstuffs, beverages and feed.  
Remove all soiled and contaminated clothing immediately.  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.
- ◆ **Breathing equipment:**  
Use suitable respirator when high concentrations are present.
- ◆ **Protection of hands:** Impervious gloves
- ◆ **Eye protection:**  
Safety glasses  
Tightly sealed goggles  
Full face protection
- ◆ **Body protection:** Protective work clothing.

### Section IX. Physical and Chemical Properties

- ◆ **Form:** Powder
- ◆ **Color:** Black
- ◆ **Odor:** Not determined
- ◆ **Melting point/Melting range:** Not determined
- ◆ **Boiling point/Boiling range:** Not determined
- ◆ **Sublimation temperature / start:** Not determined
- ◆ **Flash point:** Not applicable
- ◆ **Flammability (solid, gaseous)** Product is not flammable.
- ◆ **Ignition temperature:** Not determined
- ◆ **Decomposition temperature:** Not determined

- ◆ **Danger of explosion:**  
Product does not present an explosion hazard.
- ◆ **Explosion limits:**
- ◆ **Lower:** Not determined
- ◆ **Upper:** Not determined
- ◆ **Vapor pressure:** Not determined
- ◆ **Density:** Not determined
- ◆ **Solubility in / Miscibility with**
- ◆ **Water:** Insoluble

---

#### Section X. Stability and Reactivity

---

- ◆ **Thermal decomposition / conditions to be avoided:**  
Decomposition will not occur if used and stored according to specifications.
- ◆ **Materials to be avoided:**  
Water/moisture  
Acids  
Oxidizing agents  
Carbon dioxide
- ◆ **Dangerous reactions** No dangerous reactions known
- ◆ **Dangerous products of decomposition:** Metal oxide fume

---

#### Section XI. Toxicological Information

---

- ◆ **Acute toxicity:**  
LD/Lc50 values that are relevant for classification:  
Cerium (IV) oxide (CAS# 1306-38-3), 100%  
Oral: LD50: >5000 mg/kg (rat)  
Gadolinium oxide (CAS# 12064-62-9), 100%  
Oral: LD50: 5000 mg/kg (rat)
- ◆ **Primary irritant effect:**
- ◆ **on the skin:** Irritant to skin and mucous membranes, may be corrosive
- ◆ **on the eye:** Irritating effect, may be corrosive
- ◆ **Sensitization:** No sensitizing effects known.
- ◆ **Subacute to chronic toxicity:**  
Lanthanons can cause delayed blood clotting leading to hemorrhages. Exposure may also lead to sensitivity to heat, itching, increased awareness of odor and taste, and liver damage.  
Chronic exposure to manganese may cause impairment to the central nervous system. Symptoms include sluggishness, sleepiness, muscle weakness, loss of facial muscle control, edema, emotional disturbances, spastic gait and falling. Chronic manganese poisoning may develop after as little as three months of heavy exposure but usually cases develop after one to three years of exposure.  
Strontium has a low order of toxicity. High doses have caused changes in blood clotting factors, adrenal function and liver function.  
Corrosive materials (such as SrO) are acutely destructive to the respiratory tract, eyes, skin and digestive tract. Eye contact may result in permanent damage and complete vision loss. Inhalation may result in respiratory effects such as inflammation, edema, and chemical pneumonitis. May cause coughing, wheezing, laryngitis, shortness of breath, headache, nausea and vomiting. Ingestion may cause damage to the mouth, throat and esophagus. May cause skin burns or irritation depending on the severity of the exposure.  
Cerium salts increase the blood coagulation rate. Exposure to cerium salts may increase sensitivity to heat, itching and skin lesions. Large doses to experimental animals have caused writhing, ataxia, labored respiration, sedation, hypotension and death by cardiovascular collapse.
- ◆ **Additional toxicological information:**  
Danger through skin absorption.  
Swallowing will lead to a strong corrosive effect on mouth and throat and to the danger of perforation of esophagus and stomach.  
To the best of our knowledge the acute and chronic toxicity of this substance is not fully known.

No classification data on carcinogenic properties of this material is available from the EPA, IARC, NTP, OSHA or ACGIH.

---

#### **Section XII. Environmental Information**

---

◆ **General notes:**

Do not allow material to be released to the environment without proper governmental permits.

---

#### **Section XIII. Disposal Information**

---

◆ **Product:**

◆ **Recommendation**

Consult state, local or national regulations for proper disposal.

◆ **Uncleaned packagings:**

◆ **Recommendation:**

Disposal must be made according to official regulations.

---

#### **Section XIV. Transportation Information**

---

◆ Not a hazardous material for transportation.

◆ **DOT regulations:**

**Hazard class:** None

◆ **Land transport ADR/RID (cross-border)**

**ADR/RID class:** None

◆ **Maritime transport IMDG:**

**IMDG Class:** None

◆ **Air transport ICAO-TI and IATA-DGR:**

**ICAO/IATA Class:** None

◆ **Transport/Additional information:**

Not dangerous according to the above specifications.

---

#### **Section XV. Regulatory Information**

---

◆ **Product related hazard information:**

◆ **Hazard symbols:** Irritant, Harmful

◆ **Risk phrases:**

Irritating to eyes, respiratory system and skin.

Harmful by inhalation, in contact with skin and if swallowed.

◆ **Safety phrases:**

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Wear suitable protective clothing.

◆ **National regulations**

All components of this product are listed in the U.S. Environmental Protection Agency Toxic Substances Control Act Chemical Substance Inventory.

◆ **Information about limitation of use:**

For use only by technically qualified individuals.

This product contains manganese and is subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 and 40CFR372.

---

#### **Section XVI. Other Information**

---

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Material Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

MSDS Prepared by:

**NexTech Materials, Ltd.**  
404 Enterprise Drive  
Lewis Center, OH 43035

Vendee and third persons assume the risk of injury proximately caused by the material if reasonable safety procedures are not followed as provided for in the data sheet, and vendor shall not be liable for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed.

All persons using this product, all persons working in an area where this product is used, and all persons handling this product should be familiar with the contents of this data sheet. This information should be effectively communicated to employees and others who might come in contact with the product.

While the information accumulated and set forth herein is believed to be accurate as of the date hereof, NexTech Materials, Ltd. makes no warrant with respect thereto and disclaims all liability from reliance thereon. Recipients are advised to confirm in advance that the information is current, applicable, and suitable for their particular circumstances.